

BMW X5 2001-2007

Ref H0246

PACKING REQUIREMENTS

- BOOT LINER
Minimum x 10 self adhesive loop fastener pads
- TAILGATE COVER
Minimum 16 self-adhesive loop fastener tabs



VERY IMPORTANT PREPARATION



To ensure a good bond, when using the self-adhesive hook & loop fasteners to attach the Boot liner to the plastic / metal trim (Not the carpet); it is most important to remove silicone film from the vehicle trim. Silicone is applied during manufacture and can also be found in many valeting products. It is highly likely there will be a build-up of silicone. Before applying any self-adhesive fastener pads, the surface **MUST** be thoroughly cleaned using a silicone remover. (The fasteners cannot be used once it has been in contact with silicone). We recommend "Intensive Tar Remover" made by AutoGlym and available from Halfords. Wipe off thoroughly any residue with a separate clean dry cloth.

NOTE: the adhesive takes 24hrs to reach full adhesion, do not touch during.

FITTING

Remove load cover, it can be replaced later.

Place liner into car and unfold

BASE:

- Tailgate end: Slide the pocket over the 'Plastic hinge cover flap'.
- Position the base panel snugly into place.
- Front end: **See photo A**; At the seat end of base locate the two ties and pass them down into the void between the floor and the seat uppers. Access the second row seat base from the passenger door. Lift up the base and tie these two ties to the 'D' ring section of the seat belt catch mechanism.



Photo A
(Photo is non-specific to your car)

FRONT

Pass the four hook & loop fastener straps up and around the headrest posts and fasten back onto the liner.

REAR PLUS VERSIONS: Ensure you unfasten the headrest straps before attempting to fold the rear seats.

SIDES:

- At tailgate end: Release the small access door panels. Pass the large elastic loops over the top of these panels and slide them half way down. The small elastic loops go over the protruding plastic catches. Before closing up the door panels realign this part of the liner.
- The three tabs with hook fastener welds on each side panel: attach self-adhesive loop fastener pads to the hook fastener. Position the rest of the sides snugly into place before removing the fastener backing. Locate the two front tabs onto the horizontal part of the load space cover runners. The rear attaches to the plastic trim.

TAILGATE COVER

- Use the self-adhesive fastener pads to attach to the plastic panel.