

RENAULT CLIO III 2005 - 2012

OUR REF: Ho410

Packing requirements

- BOOT LINER
Minimum 9 self adhesive loop fastener tabs
- TAILGATE COVER
Minimum 15 self adhesive loop fastener tabs



Photo shows a Rear Plus option Liner

VERY IMPORTANT PREPARATION



To ensure a good bond, when using the self-adhesive loop fastener to attach the boot liner to the plastic / metal trim (**Not** the carpet); it is most important to remove silicone film from the vehicle trim. Silicone is applied during manufacture and can also be found in many valeting products. It is **highly likely there will be a build-up of silicone**. Before applying any loop fastener pads, the surface **MUST be thoroughly** cleaned using a silicone remover. (The hook & loop fastener cannot be used once it has been in contact with silicone). We recommend "Intensive Tar Remover" made by AutoGlym and available from Halfords. Wipe off thoroughly **any residue with a separate clean dry cloth**.

NOTE: the adhesive takes 24hrs to reach full adhesion – do not disturb during.

FITTING

- Remove load cover cassette, it can be replaced later.
- Position base of the liner snugly into place.

FRONT PANEL

- Pass the hook & loop fastener straps around the headrest posts and fasten close to the liner.
- The hook fastener welds attach directly to the carpet.

SIDE PANELS: PHOTO A.

- The hook fastener attaches directly to the carpet.
- The top edge sits under the plastic panel.
- The back edge sits under the rubber seal.

REAR PANEL.

- Use the self-adhesive loop fastener to attach the liner to the plastic panels.



Please note the following photos are non-specific to your vehicle

TAILGATE COVER

- Use the self-adhesive loop fastener tabs to attach the cover to the plastic trim.



BUMPER FLAP

- Fit boot liner
- Attach the Bumper Flap to the loop fastener strip that has been manufactured into the base of the boot liner.
- The Bumper Flap is one standard length for all models. Trim the length to suit your requirements. Ensure you do not cut through the stitching
- The Bumper Flap either folds into the vehicle OR can be detached and stored elsewhere when you close the tailgate.
- Please note that the edges of the fabric are not bound so that any mud, dirt or water can run off.



SEAT FLAP

- The Seat flap is designed to protect the top of your rear seat giving additional protection from drooling dogs etc.
- The Seat Flap can also be used in conjunction with the **Rear Plus** Option(s). With the rear seats in the folded position the Seat Flap extends the coverage over any exposed section of the seat backs and the headrests
- Attach the Seat Flap to the loop fastener strip that has been manufactured into the boot Liner just below the top of the rear seats.
- The flap is then placed over the rear head rests and down the back of the passenger seats.
- If the Seat Flap sits over large headrests and obstructs your rear view: carefully create openings in the flap to accommodate the headrest posts.

