

FITTING INSTRUCTIONS

hatchbag.co.uk

SKODA FABIA 2 + 3 HATCH 2007 on

Our ref: H0439

PACKING REQUIREMENTS

BOOT LINER

Min x 21 self-adhesive loop fastener pads 3 cut lengths of self-adhesive loop fastener: 1 @ 170mm / 1 @ 125mm / 1 @ 780mm

] TAILGATE COVER Requires no additional fixings

PREPARATION

- Remove the load cover. It may be replaced later.
- Ensure the 2nd row seats are slid to suit your order.

VERY IMPORTANT PREPARATION

To ensure a good bond, when using the self-adhesive loop fastener to attach the boot liner to the plastic / metal trim (**Not** the carpet); it is most important to remove silicone film from the vehicle trim. Silicone is applied during manufacture and can also be found in many valeting products. It is **highly likely there will be a build-up of silicone**. Before applying any loop fastener pads, the surface **MUST be thoroughly** cleaned using a silicone remover. (The loop fastener cannot be used once it has been in contact with silicone). We recommend "Intensive Tar Remover" made by AutoGlym and available from Halfords. Wipe off thoroughly **any residue with a separate clean dry cloth.**

Unfortunately, we are unable to supply this product, as it cannot be transported via our postal carrier.

NOTE: the adhesive takes 24hrs to reach full adhesion – do not disturb during.







FITTING

BASE PANEL

The hook fastener welds on the reverse side of the liner. Attach directly to the carpet.

FRONT PANEL(back of seats!)

Pass each hook & loop fastener strap around the corresponding headrest post, and fasten close back onto itself. The hook fastener welds on the reverse side of the liner attach directly to the carpet on the back of the seats.

BACK PANEL + SIDES

Use the self-adhesive loop fastener pads to attach the liner to the plastic.

See Photo A: Use the longest length of self-adhesive loop fastener to attach the back panel of the liner. See Photo B: Attach the two shorter lengths of self-adhesive loop fatener along the top edge of the plastic pocket panels.

OPTIONAL EXTRAS

REAR DOOR COVER

The hook fastener welds on the reverse side of the cover. Attach directly to the carpet.

Please note these photos are non-specific to your model

SEAT FLAP

- The Seat flap is designed to protect the top of your rear seat giving additional protection from drooling dogs etc.
- The Seat Flap can also be used in conjunction with the **Rear Plus** Option(s). With the rear seats in the folded position the Seat Flap extends the coverage over any exposed section of the seat backs and the headrests
- Attach the Seat Flap to the loop fastener strip that has been manufactured into the boot liner just below the top of the rear seats.
- The flap is then placed over the rear head rests and down the back of the passenger seats.
- If the Seat Flap sits over large headrests and obstructs your rear view: carefully create openings in the flap to accommodate the headrest posts.

BUMPER FLAP

- Fit boot liner
- Attach the Bumper Flap to the loop fastener strip that has been manufactured into the base of the boot liner.
- The Bumper Flap either folds into the vehicle OR can be detached and stored elsewhere when you close the tailgate.
- Please note that the edges of the fabric are not bound so that any mud, dirt or water can run off.





