

HYUNDAI i20 Hatch 2009 to 2014

PACKING REQUIREMENTS

- ☐ **BOOTLINER**
Minimum of 1 self-adhesive loop fastener tabs
600mm cut length of 20mm wide self adhesive
loop fastener.
600mm cut length of 50mm wide self adhesive
loop fastener.
- ☐ **REAR DOOR COVER**
Minimum of 17 self-adhesive loop fastener tabs



PREPARATION

- Remove the load cover. It can be replaced later.
- Unfold the Hatchbag and place in the vehicle so that the base fits snugly in position. The panel with the Hatchbag label sits against the back of the rear seat.

VERY IMPORTANT PREPARATION

To ensure a good bond, when using the self-adhesive hook & loop fastener to attach the Bootliner to the plastic / metal trim (**Not** the carpet); it is most important to remove silicone film from the vehicle trim. Silicone is applied during manufacture and can also be found in many valeting products. It is **highly likely there will be a build-up of silicone**. Before applying any self-adhesive fastener pads, the surface **MUST be thoroughly** cleaned using a silicone remover. (The fasteners cannot be used once it has been in contact with silicone). We recommend "Intensive Tar Remover" made by AutoGlym and available from Halfords. Wipe off thoroughly **any residue with a separate clean dry cloth**.

NOTE: the adhesive takes 24hrs to reach full adhesion – do not disturb during.



Please note the following photos are generic

FRONT

- Hook & loop fastener straps align to headrests.
- Pass around each post and fasten back onto themselves.

REAR PLUS VERSIONS

YOU MUST UNFASTEN THE HOOK & LOOP FASTENERS + THE HEADREST STRAPS BEFORE YOU RECLINE THE REAR SEAT UPPERS (Please refer to REAR PLUS options on website to see detailed photo')



SIDES

- Carefully position the side panels snugly into place.
- Use the self-adhesive loop fasteners to attach the side to the plastic trim. Attach the self-adhesive loop fastener tabs to the hook fasteners on the liner. Peel off protective backing, reposition panel and apply **FIRM** pressure at tab location point to ensure maximum adhesion to structure. Repeat for each fastener.



BACK

- Use the self-adhesive loop fasteners to attach the back to the tailgate plate.

OPTIONAL EXTRAS

TAILGATE COVER

- Use the self-adhesive loop fastener tabs to attach the cover to the plastic trim.



SEAT FLAP

- The Seat flap is designed to protect the top of your rear seat giving additional protection from drooling dogs etc.
- The Seat Flap can also be used in conjunction with the **Rear Plus** Option(s). With the rear seats in the folded position the Seat Flap extends the coverage over the seat backs and the headrests
- Attach the Seat Flap to the loop fastener strip that has been manufactured into the Boot Liner just below the top of the rear seats.
- The flap is then placed over the rear head rests and down the back of the passenger seats.



BUMPER FLAP

- Attach the Bumper Flap to the loop fastener strip that has been manufactured into the base of the boot liner.