

MINI COUNTRYMAN 2010-2017

Our Ref: H0532 LOW

REAR SEATS ARE UPRIGHT, AND SLID AS FAR BACK TO THE TAILGATE

Adjust the seat back to a relatively upright position.
(Please note: The most upright position was not chosen as it inclines forward, making it uncomfortable for passengers to sit on!)



PACKING REQUIREMENTS

- BOOT LINER**
Minimum of 2 self-adhesive loop fastener tabs
750 mm of 20 mm wide self-adhesive loop fastener.
25 of REF: 113
- REAR DOOR COVER**
Minimum of 16 self-adhesive loop fastener tabs



REF: 113

Please note: photo shows the Rear Split version

VERY IMPORTANT PREPARATION

To ensure a good bond, when using the self-adhesive loop fastener to attach the boot liner to the plastic / metal trim (**Not** the carpet); it is most important to remove silicone film from the vehicle trim. Silicone is applied during manufacture and can also be found in many valeting products. It is **highly likely there will be a build-up of silicone**. Before applying any loop fastener pads, the surface **MUST be thoroughly** cleaned using a silicone remover. (The loop fastener cannot be used once it has been in contact with silicone). We recommend "Intensive Tar Remover" made by AutoGlym and available from Halfords. Wipe off thoroughly **any residue with a separate clean dry cloth**.

Unfortunately we are unable to supply this product, as it cannot be transported via our postal carrier.

NOTE: the adhesive takes 24hrs to reach full adhesion – do not disturb during.



FREQUENT USE HOOK & LOOP FASTENER PATCHES – REF: 113

- If you frequently remove/fit your boot liner from/to your vehicle please note that the carpet will “fluff” up
- We have included a set of “Frequent Use hook & loop fastener Patches”
- Whilst fitting the boot liner “sandwich” a Patch between the carpet and the boot liner at each hook fastener weld location.
- Leave the patch attached to the carpet at all times.



REF: 113



PREPARATION

- Remove the load cover. It may be replaced later.
- Unfold the Hatchbag and place in the vehicle. The panel with the Hatchbag label sits against the back of the rear seat.

Please note not all of the photographs are specific to your vehicle

BASE

- Position the base snugly into place.
- The hook fastener welded to the reverse face of the liner will attach directly to the carpet.



FITTING FRONT

- Hook & loop fastener straps align to headrests.
- Pass around each post and fasten back onto themselves.
- Any hook fastener welded to the reverse face of the liner will attach directly to the carpet panels.



REAR PLUS VERSIONS

- **YOU MUST UNFASTEN THE HOOK & LOOP FASTENER + THE HEADREST STRAPS BEFORE YOU RECLINE THE REAR SEAT UPPERS (Please refer to REAR PLUS options on website to see detailed photo's)**



Attach the self-adhesive loop fastener to the plastic



Fasten directly to carpet

SIDES

- Carefully position the side panels snugly into place.
- The hook fastener welded to the reverse face of the liner will attach directly to the carpet panels.
- Use the pre-cut loop fastener tabs to attach the front of the side panels to the plastic trim.

Strips of self-adhesive loop fastener to the plastic



BACK

- Carefully position the back panel snugly into place.
- Cut and attach appropriate lengths of the “uncut” loop fastener to the plastic area as illustrated in this photo above.
- Use the pre-cut loop fastener tabs to attach the rest of the side panels to the plastic trim.

Please note the following photos are non-specific to your vehicle

TAILGATE COVER

- Use the self-adhesive loop fastener tabs to attach the cover to the plastic trim.



TAILGATE COVER

BUMPER FLAP

- Fit boot liner
- Attach the Bumper Flap to the loop fastener strip that has been manufactured into the base of the boot liner.
- The Bumper Flap either folds into the vehicle OR can be detached and stored elsewhere when you close the tailgate.
- Please note that the edges of the fabric are not bound so that any mud, dirt or water can run off.



BUMPER FLAP

SEAT FLAP

- The Seat flap is designed to protect the top of your rear seat giving additional protection from drooling dogs etc.
- The Seat Flap can also be used in conjunction with the **Rear Plus** Option(s). With the rear seats in the folded position the Seat Flap extends the coverage over any exposed section of the seat backs and the headrests
- Attach the Seat Flap to the fastener strip that has been manufactured into the boot liner just below the top of the rear seats.
- The flap is then placed over the rear head rests and down the back of the passenger seats.
- If the Seat Flap sits over large headrests and obstructs your rear view: carefully create openings in the flap to accommodate the headrest posts.



SEAT FLAP