

## Hyundai i30 Tourer

2012 on

Our ref: H0551

### Packing requirements

#### BOOT LINER

- Does NOT require additional fixings

#### REAR DOOR COVER

- Minimum of 20 self-adhesive loop fastener tabs



Please note: photo shows Rear Plus Boot Liner with extra fastener strips to take the additional Bumper flap + Floor Extension

### PREPARATION

Remove the load cover cassette. It can be replaced later.

### BASE

- Place the liner into the car and fit the base snugly into place.
- The hook fastener welds on the reverse face of the base panel will attach directly to the carpet.



### FITTING FRONT

- Hook & loop fastener straps align to headrests.
- Pass around each post and fasten back onto themselves.

### REAR PLUS VERSIONS

- **YOU MUST UNFASTEN THE HEADREST STRAPS BEFORE YOU RECLINE THE REAR SEAT UPPERS**  
*(Please refer to REAR PLUS options on website to see detailed photo and description)*



### SIDES

- Carefully position the side panels snugly into place.
- The hook fasteners welded to the reverse face of the liner will attach directly to the carpet panels.
- **Please ensure you carpet is free from pet hair and debris before fitting.** This will impede the grip ability of the hook fasteners to the carpet sides.



# Optional extras

*Please note not all of the photographs are specific to your vehicle*



## BUMPER FLAP

- Fit Bootliner
- Attach the Bumper Flap to the loop fastener strip that has been manufactured into the base of the boot liner.
- The Bumper Flap either folds into the vehicle OR can be detached and stored elsewhere when you close the tailgate.
- Please note that the edges of the fabric are not bound so that any mud, dirt or water can run off.



## SEAT FLAP

- The Seat flap is designed to protect the top of your rear seat giving additional protection from drooling dogs etc.
- The Seat Flap can also be used in conjunction with the Rear Plus Option(s). With the rear seats in the folded position the Seat Flap extends the coverage over any exposed section of the seat backs and the headrests
- Attach the Seat Flap to the loop fastener strip that has been manufactured into the Boot Liner just below the top of the rear seats.
- The flap is then placed over the rear head rests and down the back of the passenger seats.
- If the Seat Flap sits over large headrests and obstructs your rear view: carefully create openings in the flap to accommodate the headrest posts.



## TAILGATE COVER

### VERY IMPORTANT PREPARATION

To ensure a good bond, when using the self-adhesive fasteners to attach the Bootliner to the plastic / metal trim (Not the carpet); it is most important to remove silicone film from the vehicle trim. Silicone is applied during manufacture and can also be found in many valeting products. It is highly likely there will be a build-up of silicone. Before applying any fastener pads, the surface **MUST** be thoroughly cleaned using a silicone remover. (The fastener cannot be used once it has been in contact with silicone). We recommend "Intensive Tar Remover" made by AutoGlym and available from Halfords. Wipe off thoroughly any residue with a separate clean dry cloth.

NOTE: the adhesive takes 24hrs to reach full adhesion – do not disturb during.

- Use the self-adhesive loop fastener tabs to attach the cover to the plastic trim.

