

## BMW 2 SERIES ACTIVE 2014 to 2021

Our ref: H0596

Packing requirements

- BOOTLINER  
Requires NO additional fixings
- REAR DOOR COVER  
Minimum of 18 self-adhesive loop fastener tabs



Photo : BACK version - Rear Plus with Split Seat, prepared for a Bumper Flap

### PREPARATION

If your seats slide (Not SEFIX), please ensure that the rear seat backs are slid to suit your order – BACK or FORWARD

#### “BACK”

Rear seats are slid as far back to the tailgate as possible



#### “FORWARD”

Rear seats are slid as far forward to the front of the car as possible



Please ensure the rear seat uppers are “MOST RECLINED”



The Bootliner is **NOT** designed to suit any other seat rake position

- Remove the load cover. It may be replaced later.

## BASE

- Unfold the Hatchbag and place in the vehicle. The panel with the Hatchbag label sits against the back of the rear seat.
- Position the base of the Bootliner snugly into place.
- The hook fasteners welded to the reverse face of the base will attach directly to the carpet.



## FITTING FRONT

- Hook & Loop Fastener straps align to headrests.
- Pass around each post and fasten back onto themselves.



## REAR PLUS VERSIONS

- **YOU MUST UNFASTEN THE HOOK & LOOP FASTENER / THE HEADREST STRAPS BEFORE YOU RECLINE THE REAR SEAT UPPERS EITHER MANUALLY OR ELECTRICALLY**

(Please refer to REAR PLUS options on website to see detailed photos)



## SIDES

- Carefully position the side panels snugly into place.
- The hook fasteners welded to the reverse face of the liner will attach directly to the carpet panels.



The Bootliner is manufactured to accommodate the Offside Net



SIDE version - Rear Plus with Split Seat, prepared for a Bumper Flap

*Please note these photos are non-specific to your car.*

## OPTIONAL EXTRAS

### SEAT FLAP

- The Seat flap is designed to protect the top of your rear seat giving additional protection from drooling dogs etc.
- The Seat Flap can also be used in conjunction with the Rear Plus / Split options. With the rear seats in the folded position the Seat Flap extends the coverage over any exposed section of the seat backs and the headrests
- Attach the Seat Flap to the loop fastener strip that has been manufactured into the Boot Liner just below the top of the rear seats.
- The flap is then placed over the rear head rests and down the back of the passenger seats.
- If the Seat Flap sits over large headrests and obstructs your rear view: carefully create openings in the flap to accommodate the headrest posts



### BUMPER FLAP

- Fit Bootliner
- Attach the Bumper Flap to the loop fastener strip that has been manufactured into the base of the boot liner.
- The Bumper Flap either folds into the vehicle OR can be detached and stored elsewhere when you close the tailgate.
- Please note that the edges of the fabric are not bound so that any mud, dirt or water can run off.



### TAILGATE COVER

- Use the self-adhesive loop fastener tabs to attach the cover to the plastic trim.

## VERY IMPORTANT TAILGATE PREPARATION

To ensure a good bond, when using the self-adhesive hook & loop fasteners to attach the cover to the plastic trim it is most important to remove silicone film from the vehicle trim. Silicone is applied during manufacture and can also be found in many valeting products. It is **highly likely there will be a build-up of silicone**. Before applying any self-adhesive fastener tabs, the surface **MUST be thoroughly** cleaned using a silicone remover. (The fasteners cannot be used once it has been in contact with silicone). We recommend "Intensive Tar Remover" made by AutoGlym and available from Halfords. Wipe off thoroughly **any residue with a separate clean dry cloth**.

**NOTE:** the adhesive takes 24hrs to reach full adhesion – do not touch during.

