

NISSAN X-TRAIL 5 SEATER - 2014 - 2022

RAISED FLOOR, LOW FLOOR, SHAPE 1, SHAPE 2

OUR REF: H0621 FRSD/FLOW/SH1/SH2

PACKAGING REQUIREMENTS.

BOOT LINER

- **14x** Self Adhesive loop fastener tabs
- **2x 730mm 30mm wide** self-adhesive loop fastener

TAILGATE COVER

- **20x tabs** self-adhesive loop fastener



IMAGE ABOVE - SHAPE 2 WITH FLOOR LOWERED



VERY IMPORTANT PREPARATION



To ensure the self-adhesive hook & loop fastener stick to the plastic trim, you **MUST CLEAN** the plastic from grime and **REMOVE** all the **SILICONE** applied during manufacture and valeting.

To do this please:

1. Use a silicone remover, such as 'Auto-Glym Intensive Tar Remover' and apply generously to the surface you want to adhere to.
2. Using a separate clean & dry cloth, thoroughly dry the surface until the cloth starts to drag. Attach 1 self-adhesive fastener tab to see if it sticks. (Repeat step 1 to 2 if necessary) A couple of spares have been provided.
3. Attach the self-adhesive fasteners and let them fully adhere over the next 24 hours for the best bond.


**The self-adhesive fasteners cannot be used once it has been in contact with silicone. Replacement kits are available from our website.*



Please note not all of the photographs are specific to your vehicle


STEP 1. PREPERATIONS

- Please remove the load cover, it may be replaced once the boot liner is fitted.
- Please recline your seat so that it is 11 cm away from the load cover slot **image A**.
- Set the floor to the position as specified during your order.



STEP 2. FITTING BASE

- Place the boot liner into the car boot with the Hatchbag logo at the seat end. Flatten the base so that it fits snugly against the edges. **(image B)**
- Attach 1 self-adhesive loop fastener strip on the plastic base of the recess on both sides of the car boot. Line these up with the hook fastener welded on the underside of the boot liner base and attach. **(image C)**



STEP 3. FITTING THE FRONT

- **- PLUS / SPLIT VERSION ONLY** - fasten the hook & loop fasteners between the side panels and the seat panel. **(image D)**
- Starting with the middle headrest, fasten the hook & loop fastener straps around both headrest posts. **(image E)**. Make sure to hold the front part of the base in position as not to pull the boot liner too far up. Repeat the procedure with the left and right headrests.

REAR PLUS VERSIONS

You **MUST** unfasten the hook & loop fasteners + the headrest straps before you recline the rear seat uppers. (*Please refer to REAR PLUS / SPLIT options on website to see detailed photo*)



STEP 4. FITTING THE SIDES & BACK

- Attach the 710mm long self-adhesive loop fastener strips below the joint of the 2 plastic panels on each side of the boot (photo F) (in the photo the top panel is white and the bottom is black)
- Attach the hook fastener, sewn to the back of the liner sides, to the previously attached loop fastener strips.
- Attach 3 self-adhesive loop fastener tabs to both side panels by the boot door. Make sure the loop fastener is in line with the hook fastener welded on the back of the boot liner as shown in image G.
- Attach a further 3 loop fastener tabs on each side of the rear panel in line with the hook fastener welded onto the back of the boot liner base as shown in image H.



OPTIONAL EXTRAS

Please note the following photos are non-specific to your vehicle

STEP 5A. SEAT FLAP

- The Seat flap is designed to protect the top of your rear seat giving additional protection from drooling dogs etc.
- The Seat Flap can also be used in conjunction with the **Rear Plus** or **Split** Option(s). With the rear seats in the folded position the Seat Flap extends the coverage forward. (image 3)
- Lower the headrests
- Attach the Seat Flap to the loop fastener strip that has been manufactured into the Boot liner just below the top of the rear seats. (image 1)
- The flap is then placed over the rear head rests and down the back of the passenger seats. (image 2)
- If the Seat Flap sits over large headrests and obstructs your rear view: carefully create openings in the flap to accommodate the headrest posts.



STEP 5B. TAILGATE COVER

- Line up the tailgate cover with the tailgate and clean the areas where the self-adhesive loop fastener tabs will be stuck. (image 4)



Use the self-adhesive loop fastener tabs to attach the cover to the plastic trim.

STEP 5C. BUMPER FLAP

- Fit boot liner
- Attach the Bumper Flap to the loop fastener strip that has been manufactured into the base of the boot liner. (image 5)
- The Bumper Flap either folds into the vehicle OR can be detached and stored elsewhere when you close the tailgate.

OPTIONAL EXTRAS page 2

Please note the following photos are non-specific to your vehicle

STEP 5D. FLOOR EXTENSION

The “Floor extension” offers superior protection to the rear seats when purchased in conjunction with a REAR PLUS option.(image 6)

- The Floor extension is designed to attach to a Rear Plus version liner.
- It offers additional protection to the back of the front seats and the extended floor area when the rear seats are folded flat.
- The max width is 148cm (see photo on left).
- It will offer no protection to the rear doors



The Seat Flap 5A, The Bumper Flap 5C & The Floor Extension 5D cannot be added at a late date