



Ford Galaxy - 2015 Onwards

7 seater - 3rd row folded

our ref: H0723

Packaging requirements:

BOOT LINER

- 1 x 960 mm 30mm wide self-adhesive loop fastener
- 1 x 670 mm 30mm wide self-adhesive loop fastener
- 1 x 230 mm 30mm wide self-adhesive loop fastener
- 14 x tabs self-adhesive loop fastener
- 4 x ref 117



28 x tabs self-adhesive loop fastener



Boot liner with rear split prepped for a seat flap, bumper flap & boot liner extension





VERY IMPORTANT PREPARATION



To ensure the self-adhesive hook & loop fastener stick to the plastic trim, you MUST CLEAN the plastic from grime and REMOVE all the SILICONE applied during manufacture and valeting.

To do this please:

- Use a silicone remover, such as 'Auto-Glym Intensive Tar Remover' and apply generously to the surface you want to adhere to.
- Using a separate clean & dry cloth, thoroughly dry the surface until the cloth starts to drag. Attach 1 self-adhesive fastener tab to see if it sticks. (Repeat step 1 to 2 if necessary) A couple of spares have been provided.
- Attach the self-adhesive fasteners and let them fully adhere over the next 24 hours for the best bond.

*The self-adhesive fasteners cannot be used once it has been in contact with silicone. Replacement kits are available from our website.





19/03/2019 | v. 01 page. 1

STEP 1. PREPARATIONS

- Fold the 3rd row seats flat, they can not be used with the boot liner fitted.
- Set the 2nd row seat backs to a fully upright position. (blue highlight - Image A)
- Slide the 2nd row seats as far back to the tailgate as possible. (orange highlight - Image A)
- Secure both of the 3rd row seat belts to the sides of the boot in the following positions;


(this is to ensure the boot liner sits tighter to the boot sides)

- 1. Fasten the bottom of the seatbelts to the side carpeted area (just above the base) using the ref.117 tabs. (Image B)
- Fasten the top of the seatbelts to the plastic panel using the remaining ref. 117 tabs. To attach these to the plastic you will need to stick 2 self-adhesive loop fastener tabs to both sides of the seatbelt. (Image C & D)











STEP 2. FITTING THE BASE

Place the boot liner into the car boot with the Hatchbag logo at the seat end. Flatten the base so it fits snugly against the edges. The hook fasteners welded to the reverse face fix directly to the carpet. (image E)



STEP 3. FITTING THE FRONT

- PLUS / SPLIT VERSION ONLY fasten the hook & loop fasteners between the side panels and the seat panel. (image F)
- Starting with the middle headrest, fasten the hook & loop fastener straps around both headrest posts.
 (image G). Make sure to hold the front part of the base in position as not to pull the boot liner too far up. Repeat the procedure with the left and right headrests.



You MUST unfasten the hook & loop fasteners +
the headrest straps before you recline the rear seat
uppers. ('Please refer to REAR PLUS / SPLIT
options on website to see detailed photo')





STEP 4. FITTING THE SIDES & BACK



Attach the 960mm long self-adhesive loop fastener strip to the nearside plastic panel going below the load cover slots. (Image H)



Repeat with the offside using the 670mm and the 230mm loop fastener strips that go both sides of the circular vent. (Image I)



Attach 1 loop fastener tab to the rear facing narrow plastic panels on both sides of the boot (yellow arrow) in line with the hook fasteners sewn onto the boot liner sides.(Image H & I)



Attach 4 self-adhesive loop fastener tabs to the plastic panel on both sides of the tailgate lock in line with the hook fasteners welded onto the boot liner. (Image J)

 Fasten the boot liner to the previously attached loop fasteners and the carpeted boot sides. Its easiest to start at the back of the boot moving forward. (white arrow, image K)









OPTIONAL EXTRAS

Please note the following photos are non-specific to your vehicle

STEP 5A. SEAT FLAP

- The Seat flap is designed to protect the top of your rear seat giving additional protection from drooling dogs etc.
- The Seat Flap can also be used in conjunction with the Rear Plus or Split Option(s). With the rear seats in the folded position the Seat Flap extends the coverage forward. (image 3)
- Lower the headrests
- Attach the Seat Flap to the loop fastener strip that has been manufactured into the Boot liner just below the top of the rear seats. (image 1)
- The flap is then placed over the rear head rests and down the back of the passenger seats. (image 2)
- If the Seat Flap sits over large headrests and obstructs your rear view: carefully create openings in the flap to accommodate the headrest posts.

STEP 5B. TAILGATE COVER



Line up the tailgate cover with the tailgate and clean the areas where the self-adhesive loop fastener tabs will be stuck. (image 4)

• Use the self-adhesive loop fastener tabs to attach the cover to the plastic trim.

STEP 5C. BUMPER FLAP

- Fit boot liner
- Attach the Bumper Flap to the loop fastener strip that has been manufactured into the base of the boot liner. (image 5)
- The Bumper Flap either folds into the vehicle OR can be detached and stored elsewhere when you close the tailgate.











OPTIONAL EXTRAS page 2

Please note the following photos are non-specific to your vehicle

STEP 5D. FLOOR EXTENSION

The 'Floor extension' offers superior protection to the rear seats when purchased in conjunction with a REAR PLUS option. (image 6 & 7)

- The Floor extension is designed to attach to a Rear Plus/Split version liner.
- It offers additional protection to the back of the front seats and the extended floor area when the rear seats are folded flat.
- It will offer no full protection to the rear doors
- Attach the floor extension to the main boot liner (Image 6)
- Fasten the two ties in the corner together (Orange arrows - Image 7)
- Fasten the hook & loop fastener straps around both headrest posts. (Blue arrows - Image 7)

The Seat Flap 5A, The Bumper Flap 5C & The Floor Extension 5D cannot be added at a late date

STEP 5E. FREQUENT USE KIT

 If you frequently remove/fit your boot liner from/to your vehicle please note that the carpet will "fluff" up – we have an alternative "Frequent Use Fitting Kit" (image 8+9)

The Frequent Use Kit is available to buy from our "on-line" Factory Shop – simply add it to your order from the Factory Shop. These can also be ordered at a later date.







