

Renault Koleos – 2017 to 2020

our ref: H0729

Packaging requirements:

☐ BOOT LINER

- 2 x 410 mm 30mm wide self-adhesive loop fastener
- 28 x ref:113 Frequent use tabs

☐ TAILGATE COVER

- 22 x tabs self-adhesive loop fastener



Rear Plus with Seat Split boot liner prepped for a seat flap, bumper flap and Bootliner Extension



REF:113



VERY IMPORTANT PREPARATION



To ensure the self-adhesive hook & loop fastener stick to the plastic trim, you **MUST CLEAN** the plastic from grime and **REMOVE** all the **SILICONE** applied during manufacture and valeting.

To do this please:

1. Use a silicone remover, such as 'Auto-Glym Intensive Tar Remover' and apply generously to the surface you want to adhere to.
2. Using a separate clean & dry cloth, thoroughly dry the surface until the cloth starts to drag. Attach 1 self-adhesive fastener tab to see if it sticks. (Repeat step 1 to 2 if necessary) A couple of spares have been provided.
3. Attach the self-adhesive fasteners and let them fully adhere over the next 24 hours for the best bond.

**The self-adhesive fasteners cannot be used once it has been in contact with silicone. Replacement kits are available from our website.*



Please note not all of the photographs are specific to your vehicle

STEP 1. PREPARATIONS

- Remove the load cover. It may be replaced later.

STEP 2. FITTING THE BASE

- Place the boot liner into the car boot with the Hatchbag logo at the seat end. Flatten the base so it fits snugly against the edges. The hook fasteners welded to the reverse face fix directly to the carpet. (image A)
- Starting in the left hand corner behind the rear seats : carefully peel back the base to expose the hook fastener and fix to the exposed carpet one ref:113 in-line with where the fastener had been attached. (image B)
- Repeat for all 6 hook fasteners on the base panel.



NOTE: When occasionally removing the boot liner, peel the boot liner away from the ref:113 leaving it attached to the car boot. This will prevent the carpet fibres from fluffing up, and reducing the functionality of the fasteners.



STEP 3. FITTING THE FRONT

- - **PLUS / SPLIT VERSION ONLY** - fasten the hook & loop fasteners between the side panels and the seat panel. (image C)
- Starting with the middle headrest, fasten the hook & loop fastener straps around both headrest posts. (image D). Make sure to hold the front part of the base in position as not to pull the boot liner too far up. Repeat the procedure with the left and right headrests.

REAR PLUS VERSIONS

- You **MUST** unfasten the hook & loop fasteners + the headrest straps before you recline the rear seat uppers. ('Please refer to **REAR PLUS / SPLIT** options on website to see detailed photo')



STEP 4. FITTING THE SIDES

- Fasten the hook fastener sewn & welded onto the top edge of the boot liner sides directly onto the carpet along the top edge of the carpeted boot sides. (image E)
- Starting at the tailgate end of the sides : carefully peel back the boot liner to expose the carpet and fix one ref:113 in-line with where the hook fastener had been attached. (image F)
- Re-fasten the Boot liner side panel to the ref:113 tabs.(image G)



Please refer to Step 2 note.

IMAGE E



IMAGE F




IMAGE G



STEP 5. FITTING THE BACK



Stick the 30mm wide self-adhesive loop fastener onto the plastic located on both sides of the lock at the tailgate end of the boot. Fasten the boot liner to it using the hook fastener welded onto it. (Image H)

IMAGE H



OPTIONAL EXTRAS

Please note the following photos are non-specific to your vehicle

STEP 5A. SEAT FLAP (+TAILORED)

- The **Tailored** Seat flap is designed to protect the top of your rear seat giving additional protection from drooling dogs etc. (image 1)
- Lower the headrests
- Attach the Tailored Seat Flap to the loop fastener strip that has been manufactured into the Boot liner just below the top of the rear seats.
- The additional Seat Flap is designed **only** to be used in conjunction with the **Rear Plus/Split**. With the rear seats in the folded position the Seat Flap extends the coverage over any exposed section of the seat backs and the headrests. (image 2)



STEP 5B. TAILGATE COVER

- Line up the tailgate cover with the tailgate and clean the areas where the self-adhesive loop fastener tabs will be stuck. (image 3)
- Use the self-adhesive loop fastener tabs to attach the cover to the plastic trim.



STEP 5C. BUMPER FLAP

- Fit boot liner
- Attach the Bumper Flap to the loop fastener strip that has been manufactured into the base of the boot liner. (image 4)
- The Bumper Flap either folds into the vehicle OR can be detached and stored elsewhere when you close the tailgate.



OPTIONAL EXTRAS page 2

Please note the following photos are non-specific to your vehicle

STEP 5D. FLOOR EXTENSION

The 'Floor extension' offers superior protection to the rear seats when purchased in conjunction with a REAR PLUS option. (image 6 & 7)

- The Floor extension is designed to attach to a Rear Plus/Split version liner.
- It offers additional protection to the back of the front seats and the extended floor area when the rear seats are folded flat.
- It will offer no full protection to the rear doors
- Attach the floor extension to the main boot liner (Image 6)
- Tie the two laces in the corner together (Orange arrows - Image 7)
- Fasten the hook & loop fastener straps around both headrest posts. (Blue arrows—Image 7)



The Seat Flap 5A, The Bumper Flap 5C & The Floor Extension 5D cannot be added at a late date