

# Fitting Instructions

hatchbag.co.uk

# Ford Kuga - 2020 Onwards

our ref: H0792

#### FITTING KITS CONTENTS

- 2 x 570 mm 30mm wide self-adhesive loop fastener
- 2 x 140 mm 30mm wide self-adhesive loop fastener
- 1 x 190 mm 30mm wide self-adhesive loop fastener
- 2 x 300 mm 30mm wide self-adhesive loop fastener
- 1 x 140 mm 20mm wide self-adhesive loop fastener
- 4 x tabs self-adhesive loop fastener



Split boot liner prepped for a boot liner extension, seat flap and bumper flap

#### J TAILGATE COVER

20 x tabs self-adhesive loop fastener



To ensure the self-adhesive hook & loop fastener stick to the plastic trim, you MUST CLEAN all grime from the plastic and REMOVE all SILICONE applied during manufacture and valeting.

To do this please:

- 1. Use a silicone remover, such as AutoGlym Intensive Tar Remover, and apply generously to the surface you want to adhere to.
- 2. Using a separate clean, dry cloth, thoroughly dry the surface until the cloth starts to drag. Attach one self-adhesive fastener tab to see if it sticks. (Repeat steps 1 and 2 if necessary.) Extra tabs have been provided.
- 3. Attach the self-adhesive fasteners and let them fully adhere over the next 24 hours for the best bond.

\*The self-adhesive fasteners cannot be used once they have been in contact with silicone. Replacement kits are available on our website.





#### STEP 1. PREPARATIONS

- Remove the load cover. It may be replaced later.
- Slide the rear seats as far back to the tailgate as possible.
- Put the headrests in their highest position.



#### STEP 2. FITTING THE BASE

• Place the boot liner into the car boot with the Hatchbag logo at the seat end. Flatten the base so it fits snugly against the edges. The hook fasteners on the underside attach directly to the carpet. (Image B)



#### STEP 3. FITTING THE FRONT

- PLUS / SPLIT VERSION ONLY Fasten the hook & loop fasteners between the side panels and the seat panel. (Image C)
- Starting with the middle headrest, fasten the hook & loop fastener straps around both headrest posts. (Image D). Make sure to hold the front part of the base in position to avoid pulling the boot liner too far up. Repeat the procedure with the left and right headrests.

#### **REAR PLUS VERSIONS**

You MUST unfasten the hook & loop fasteners and the headrest straps before you recline the upper part of the rear seats. (*Please refer to REAR PLUS / SPLIT options on website to see detailed photo.*)



### **STEP 4.** FITTING THE SIDES



- Push the liner inside the pockets (white arrows - image G & H)
- On both sides of the boot stick the following loop fasteners in line with the hook fasteners sewn & welded on the reverse side of the boot liner as shown highlighted on image E & F.
  - Green 570 mm loop fastener
  - Orange 140 mm loop fastener
  - Pink 190 mm loop fastener
  - Yellow loop fastener tabs
  - Blue 140 mm (16mm width) loop fastener
- If necessary snip the self-adhesive fastener strips at the corners to ease around the curves.
- Fasten the hook fastener sewn onto the top and back edge on both sides of the boot liner directly onto the previously attached loop fasteners. (image E & F)










#### STEP 5. FITTING THE BACK

- Stick 2 x 300mm self-adhesive loop fasteners onto the plastic panel located on both sides at the tailgate end of the boot (highlighted in blue - image I). Fasten the boot liner to them using the hook 山
  - fastener sewn on the reverse side of the boot liner.



# **OPTIONAL EXTRAS**

Please note: the following photos are not specific to your vehicle.

#### STEP 5A. SEAT FLAP

The Seat flap is designed to protect the top of your rear seat giving additional protection from drooling dogs etc.

- Lower the headrests
- Attach the Seat Flap to the loop fastener strip that has been manufactured into the Boot liner just below the top of the rear seats. (Image 1)
- The flap is then placed over the rear head rests and down the front of the passenger seats. (Image 2)
- If the Seat Flap sits over large headrests and obstructs your rear view: carefully create openings in the flap to accommodate the headrest posts.
- The Seat Flap can also be used in conjunction with the **Rear Plus** or **Split** Option(s). With the rear seats in the folded position the Seat Flap extends the coverage forward. (Image 3)

### STEP 5B. TAILGATE COVER

Line up the tailgate cover with the tailgate and clean the areas where the self-adhesive loop fastener tabs will be stuck. (Image 4)

Use the self-adhesive loop fastener tabs to attach the cover to the plastic trim.

#### STEP 5C. BUMPER FLAP

- Fit the boot liner
- Attach the Bumper Flap to the loop fastener strip located at the base of the boot liner. (Image 5)
- The Bumper Flap either folds into the vehicle OR can be detached and stored elsewhere when you close the tailgate.



# **OPTIONAL EXTRAS PAGE 2**

Please note: the following photos are not specific to your vehicle.

#### STEP 5D. BOOTLINER EXTENSION

The Bootliner extension provides superior protection for the rear seats when purchased with a REAR PLUS option. (image 6 & 7)

- The boot liner extension is designed to attach to a Rear Plus/Split version liner.
- It provides additional protection for the back of the front seats and the extended floor area when the rear seats are folded flat.
- It does not offer full protection to the rear doors
- Attach the boot liner extension to the main boot liner (Image 6)
- Fasten the two ties in the corner together (Orange arrows Image 7)
- Fasten the hook & loop fastener straps around the headrest posts. (Blue arrows Image 7)
- Stick one self adhesive tab on the side of the boot. (highlighted in green - image 8) Attach the hook fastener tab welded on the back corner of the boot liner extension to the previously mentioned tab (White arrow - image 8)
- Repeat on opposite side

Please Note: The Seat Flap 5A, the Bumper Flap 5C & the Bootliner Extension 5D cannot be added at a later date.





