



Tesla Model 3 - 2017 Onwards

Our ref: H0824

FITTING KIT CONTENTS:

BOOT LINER

- 2 x 240 mm 30mm wide self-adhesive loop
- 3 x tab self-adhesive loop fastener
- TAILGATE COVER
- 21 x tab self-adhesive loop fastener



Rear Plus with Seat Split boot liner prepped for a seat flap, bootliner extension and bumper flap.



VERY IMPORTANT PREPARATION



To ensure the self-adhesive hook & loop fastener stick to the plastic trim, you MUST CLEAN all grime from the plastic and REMOVE all SILICONE applied during manufacture and valeting.

To do this please:

- Use a silicone remover, such as AutoGlym Intensive Tar Remover, and apply generously to the surface you want to adhere to.
- Using a separate clean, dry cloth, thoroughly dry the surface until the cloth starts to drag. Attach one self-adhesive fastener tab to see if it sticks. (Repeat steps 1 and 2 if necessary.) Extra tabs have been provided.
- Attach the self-adhesive fasteners and let them fully adhere over the next 24 hours for the best bond.

*The self-adhesive fasteners cannot be used once they have been in contact with silicone. Replacement kits are available on our website.





10/03/2022 | v. 0 pagina 1

STEP 1. PREPARATIONS

- PLUS / SPLIT VERSION ONLY Fasten the hook & loop fasteners between the side panels and the seat panel. (Image A)
- Fold the rear passenger seats.



STEP 2. FITTING THE BASE

 Place the boot liner into the car boot with the Hatchbag logo at the seat end. Flatten the base so it fits snugly against the edges. The hook fasteners on the underside attach directly to the carpet. (Image B)



Image B

STEP 3. FITTING THE BACK



On both sides of the boot stick the following loop fasteners in line with the hook fasteners sewn & welded on the reverse side of the boot liner as highlighted on (Image C, D & E)



- Green 240 mm loop fastener
- Yellow 3 x tabs self-adhesive loop fasteners
- Stick the 240mm self-adhesive loop fasteners onto the plastic panel located on both sides at the tailgate end of the boot (highlighted in green - image F).
- Stick 1 self-adhesive fastener tab to the inside center of the back panel, aligned with the hook fastener on the back panel of the boot liner. (highlighted in yellow - Image D)
- Fasten the boot liner to them using the hook fastener sewn and welded on the reverse side of the boot liner.







STEP 4. FITTING THE SIDES

- Fasten the hook fastener sewn and welded onto the top edge of the boot liner side directly onto the top edge of the carpeted boot sides. (image F)
- Push the liner into the pockets (green arrow image G)
- Fasten the hook fastener sewn and welded onto the back edge of the boot liner side directly onto the back edge of the carpeted boot sides.
- To easily fit the liner. First fit the back part of the liner as shown in image F & G. Then with the rear seats folded, fit the front part of the boot liner side. (image H).
- Once completed both sides, it should look like image I.









STEP 5. FITTING THE FRONT

- Fold the seats back. (image J)
- Ensure the liner at the front is snug fit around the edges.
- Fasten the hook fastener sewn and welded onto the top edge of the boot liner front directly onto the top edge of the carpeted seat panels. (image K)









OPTIONAL EXTRAS

Please note: not all of the photographs are specific to your vehicle.

STEP 6A. SEAT FLAP

Note: This product is only usable when seats are folded down, to protect the headrests

- Attach the Seat Flap to the loop fastener strip that has been manufactured into the Boot liner just below the top of the rear seats. (Image 1)
- The flap is then placed over the rear head rests and down the front of the passenger seats. (Image 2)
- The Seat Flap can also be used in conjunction with the Rear Plus or Split Option(s). With the rear seats in the folded position the Seat Flap extends the coverage forward.



- Line up the tailgate cover with the tailgate and clean the areas where the self-adhesive loop fastener tabs will be stuck. (Image 3)
- Use the self-adhesive loop fastener tabs to attach the cover to the plastic trim.



- Fit the boot liner
- Attach the Bumper Flap to the loop fastener strip located at the base of the boot liner. (Image 4)
- The Bumper Flap either folds into the vehicle OR can be detached and stored elsewhere when you close the tailgate.









OPTIONAL EXTRAS PAGE 2

Please note: not all of the photographs are specific to your vehicle.

STEP 6D. BOOTLINER EXTENSION

The Bootliner extension provides superior protection for the rear seats when purchased with a REAR PLUS option.

- The Bootliner extension is designed to attach to a Rear Plus/Split version liner.
- It provides additional protection for the back of the front seats and the extended floor area when the rear seats are folded flat
- It does not offer full protection to the rear doors
- Attach the Bootliner extension to the main boot liner (Image 5)
- Fasten the two ties in the corner together (Orange arrows - Image 6)
- Fasten the hook & loop fastener straps around the headrest. (Blue arrows - Image 6)
- Attach the Velcro tab welded directly to the carpet on the boot side (Green arrow - Image 7)
- Repeat on opposite side

Please Note: the Seat Flap, the Bumper Flap & the Bootliner Extension cannot be added at a later date.

STEP 6E. FREQUENT USE KIT

• If you frequently remove/install your boot liner from/to your vehicle, please note that the carpet will "fluff" up – we offer an alternative Frequent Use Fitting Kit. These tabs are placed between the boot liner and the boot carpet.(Image 8 & 9)

The Frequent Use Kit is an accessory available to purchase from our on-line store.









