

Land Rover Range Rover - 2020 Onwards 5 Seater

Our ref: H0845-DGA

FITTING KIT CONTENTS:

- BOOT LINER
 - 2 x 850 mm 30mm wide self-adhesive loop fastener
 - 2 x tabs self-adhesive loop fastener
 - 4 x REF: 121 loop fastener

- TAILGATE COVER
 - 20 x tabs self-adhesive loop fastener

- DROP DOWN TAILGATE COVER
 - 2 x 230mm 30mm wide self-adhesive loop fastener
 - 1 x 1040 30mm wide self-adhesive loop fastener
 - 7 x tabs self-adhesive loop fastener

- BOOTLINER EXTENSION
 - 2 x tabs self-adhesive loop fastener



Rear Plus with Seat Split boot liner prepped for a seat flap, boot liner extension and bumper flap.



Ref:121



VERY IMPORTANT PREPARATION



To ensure the self-adhesive hook & loop fastener stick to the plastic trim, you **MUST CLEAN** all grime from the plastic and **REMOVE** all **SILICONE** applied during manufacture and valeting.

To do this please:

1. Use a silicone remover, such as AutoGlym Intensive Tar Remover, and apply generously to the surface you want to adhere to.
2. Using a separate clean, dry cloth, thoroughly dry the surface until the cloth starts to drag. Attach one self-adhesive fastener tab to see if it sticks. (Repeat steps 1 and 2 if necessary.) Extra tabs have been provided.
3. Attach the self-adhesive fasteners and let them fully adhere over the next 24 hours for the best bond.

**The self-adhesive fasteners cannot be used once they have been in contact with silicone. Replacement kits are available on our website.*



Please note: not all of the photographs are specific to your vehicle.

STEP 1. PREPARATIONS

- Remove the load cover. It may be replaced later.
- Fold the rear seat backs flat.
- Place the boot liner in the car boot with the Hatchbag logo at the seat end. Flatten the base so it fits snugly against the edges. (Image A)



STEP 2. FITTING BASE

- Lift the hinge flap at the tailgate end and insert it in the pocket sewn on the under side of the liner's base. (Image B)
- Feed the front panel through the gap between the boot floor and the dog guard, until the D-ring cut-outs in the liner base slot into position around the dog guard's anchor rods. (Image C)



STEP 3. FITTING THE SIDES



- Cut 1 x 850 mm 30mm wide self-adhesive loop fastener to shape and attach to the bottom edge of the plastic side panels just above the carpeted area. (highlighted in orange, Image D)
- Attach 1x loop fastener tab to the plastic element on the bottom end of the boot side (blue, Image D)
- Insert 2x ref:121 fastener tabs at the tailgate end of the boot (green, Image D). To do this, peel back the rubber seal and slot the plastic end of the fastener tabs into the void behind the carpeted panel of the boot area (Image E & F)
- Slide these fastener tabs up or down so that they align with the hook fastener on the reverse side of the boot liner.
- Attach the hook fasteners sewn and welded on the reverse side of the the boot liner to the loop fasteners fixed in place previously.
- Repeat on the other side.



STEP 4. FITTING THE FRONT

- Fasten the hook & loop fasteners between the side panels and the front panel. (Image G)
- Push the two foam-filled tabs sewn onto the front end of the base into the slot between the base and the rear seats. Be sure to keep the base straight. Fold the seats back up trapping the foam tabs. (Image H)
- Loop the elastic fastener straps around each set of headrest posts. (Image I).



PLEASE NOTE

- You **MUST** unfasten the hook & loop fasteners and the headrest straps before you fold the upper part of the rear seats. (Please refer to REAR PLUS / SPLIT options on website to see detailed photo.)

OPTIONAL EXTRAS

Please note: not all of the photographs are specific to your vehicle.


STEP 6A. SEAT FLAP & TAILORED SEAT FLAP

- The Tailored Seat flap is designed to protect the top of your rear seat giving additional protection from drooling dogs etc. (Image 1)
- Lower the headrests
- Attach the Tailored Seat Flap to the loop fastener strip on the Boot liner just below the top of the rear seats. (Image 2)
- The Rectangular Seat Flap is designed **only** to be used in conjunction with the **Rear Plus/Split**. With the rear seats in the folded position this flap extends the coverage over the exposed section of the seat backs and the headrests. (Image 3)



STEP 6B. TAILGATE COVER & DROP DOWN TAILGATE COVER

- Line up both tailgate covers and clean the areas where the self-adhesive loop fastener tabs need to be placed. The drop down tailgate (Image 4) cover further requires:

-  2 x 280 mm 30mm wide self-adhesive loop fastener
- 1 x 1040 mm 30mm wide self-adhesive loop fastener
- Use the self-adhesive loop fastener tabs to attach the covers to the plastic / metal trim (Image 4&5)

STEP 6C. BUMPER FLAP

- Attach the Bumper Flap to the loop fastener strip located at the base of the boot liner. (Image 6)
- The Bumper Flap either folds into the vehicle OR can be detached and stored elsewhere when you close the tailgate.



OPTIONAL EXTRAS PAGE 2

Please note: not all of the photographs are specific to your vehicle.

STEP 6D. BOOTLINER EXTENSION

The Bootliner extension provides superior protection for the rear seats when purchased with a REAR PLUS option.

- The Bootliner extension is designed to attach to a Rear Plus/Split version liner.
- It provides additional protection for the back of the front seats and the extended floor area when the rear seats are folded flat.
- It does not offer full protection to the rear doors
- Attach the Bootliner extension to the main boot liner (Image 7)
- Fasten the two ties in the corner together by the front seats (Orange arrows - Image 8)
- Fasten the hook & loop fastener straps around the headrest posts. (Blue arrows - Image 8)



- Place 1x self-adhesive loop fastener tab where the rear seat back would lock into the upright position, (Green arrow - Image 9) attach the corresponding hook fastener welded on to the extension. (Image 10)
- Repeat on opposite side.

Please Note: the Seat Flap, the Bumper Flap & the Bootliner Extension cannot be added at a later date.

