

## UK H0849





**BMW X5** 

2019 Onwards

\*Please be aware that your boot liner may be different depending on your options/extras selection

"quantity x length / width" in mm

Before you fit the bootliner

To ensure the self-adhesive fasteners securely adhere, it's **absolutely essential** to thoroughly **eliminate** any **silicone** residues left from manufacturing and valeting processes.

To achieve this you will need a silicone remover. We recommend Autoglym® Instensive Tar Remover\*

\*can be purchased from Halfords / Amazon amongst other retailers.

Preparations

-Ensure your boot floor and seats are set to match your order.

-Remove the load cover. It may be replaced later.

-Slide the seats as far back to the tailgate, if applicable.





1

Where you find this symbol the bootliner's hook fastener will attach directly to the carpet (1)

When this is not suitable, we provide self-adhesive loop fasteners to stick onto plastic/metal trim:



Where you find this symbol, follow these steps:

- 1) Apply *Autoglym*® *Intenisve Tar remover*\* generously to a cloth and scrub the highlighted surface areas.
- 2) Dry surface thoroughly with a separate cloth until it drags.
- 3) Test the surface by attaching one fastener tab it should stick well, if not repeat previous steps<sup>(2)</sup>



Silicone is used during car manufacturing/valeting, it will interfere with the adhesion.

\*can be purchased from Halfords / Amazon amongst other retailers.

#### Tips:

- <sup>(1)</sup> If you frequently remove your boot liner from your vehicle consider our *Frequent Use Fitting Kit* to prevent carpet fluffing, available for purchase from our accesories page.
- <sup>(2)</sup> If temperatures are low, run your car for a little bit so that the boot reaches room temperature or fit your liner once you have been out for a drive.
- For optimal adhesion of the fasteners, do not remove the bootliner for approx. 48 hours.

Notes:

- The adhesive fasteners *cannot be used once they have been in contact with silicone.* Replacement Fitting kits can be purchased from our accesories page.
- Adherence to the instructions will affect the performance of the Fitting kit. Please note The Hatchbag Company will not accept requests for free replacements if the adhesive come loose after use.

Refer to colour code in the first page Fitting Kit Contents





-Fold the rear seats in preparation for next step Insert the tabs into the void between seat & base (2.3)

-Ensure the base is alligned to fit the boot edges.



-Fasten the headrest straps without pulling the base off the floor.



You MUST unfasten the headrest straps if you fold the rear seats later!



\*Please be aware that your boot liner may be different depending on your options/extras selection

Tips:

- Commence fitting from the tailgate end.
- For rear plus versions, fasten the side to the front panel from bottom to top

# **Optional extras**

Note: not all the photos are specific to your vehicle

### Bumper flap

-Attach the Bumper Flap to the loop fastener strip located on the base of the boot liner.





Seat flap

-Lower the headrests.

-Attach the Seat Flap to the loop fastener strip located just below the headrest straps.

Tailgate cover



-Line up the tailgate cover with the tailgate and clean the areas where the self-adhesive loop fastener tabs will be stuck.

-Begin with the central top and bottom fastener.





### **Bootliner Extension**

- 1. Attach the Boot liner extension to the main boot liner.
- 2. Fasten the hook & loop fastener straps around the head-rest posts.
- 3. Fasten the two ties in the corner together.
- 4. Fasten ties to the corresponding rear seat striker loop

Lower Tailgate Cover



-Line up the tailgate cover with the tailgate and clean the areas where the self-adhesive loop fasteners will be stuck.

